



PERFECT FIT



Bolloré, Inc.
60 Louisa Viens Dr
Dayville, CT 06241
Sales: 800-343-0358
www.bolloréinc.com



Rev. 1, 2022

Bolphane® BTT+125

High Speed Polyolefin ShrinkFilm

- Enhanced stiffness for high speed machine compatibility
- Instant sealing
- High shrink characteristics at low temperature
- Hot slip properties
- Excellent optics & appearance
- Recycling Code



Bolphane® BTT+125 is ideally suited for application where high speed packaging equipment is running. Exceptional shrink characteristics on irregular shaped items.

Bolphane® BTT+125 can be successfully used in applications ranging from multimedia to publishing items as well as office supplies.

TECHNICAL FEATURES

Gauge	48		
Length of the roll (feet)	Singlewound Centerfolded		
	11,660	5,830	
Gloss (20°)	114		
Haze (%)	3		
	LD*	TD**	
Elongation at break (%)	100	110	
Tensile strength (kg/cm ²)	1 150	1 100	
Free Shrink(%)	at 200°F	30	38
	at 250°F	66	67

* LD: Longitudinal Direction – ** TD: Transverse Direction

» Please contact us for any specific request.

60, Louisa Viens Drive
P.O. Box 530 - Dayville, CT 06241-0530
Sales: 800-343-0358 • Tel: 860-774-7431
Fax: 860-774-8895 • www.bollloreinc.com



Bolloré