



Bolphane[®]
ShrinkFilm

PERFECT FIT



Bolloré

Bollore Inc.
60 Louisa Viens Dr.
Dayville, CT 06241
Sales: 800-343-0358
www.bolloreinc.com

Rev. 1, 2022

Bolphane® **BTTX110**

Thin Cross-linked ShrinkFilm

- Superior impact strength
- Same mechanical properties as a conventional 15µm polyolefin film
- Broad operating window allowing use on a wide range of equipment
- High seal strength
- Excellent cohesion strength
- Improved shrinkage output due to standard perforation.

Recycling Code



Bolphane® BTTX110 is manufactured from a proprietary cross-linked process and is formulated with high-tech resins – such as the latest generation of metallocenes.

Bolphane® BTTX110 is a very forgiving film and is suitable for a wide range of product applications.

TECHNICAL FEATURES

Gauge	40	
Length of the roll (feet)	Singlewound	13,120
	Centerfolded	6,560
Gloss at 20°	115	
Haze (%)	3,5	
	LD*	TD**
Elongation at break (%)	110	120
Tensile strength (kg/cm ²)	1 400	1 500
Free Shrink(%)	at 200°F	20
	at 250° F	73

* LD: Longitudinal Direction – ** TD: Transverse Direction

» Please contact us for any specific request.

60, Louisa Viens Drive
P.O. Box 530 - Dayville, CT 06241-0530
Sales: 800-343-0358 • Tel: 860-774-7431
Fax: 860-774-8895 • www.bolloreinc.com



Bolloré