



Bolphane[®]

ShrinkFilm

PERFECT FIT



60 Louisa Viens Dr
Dayville, CT 06241
Sales: 800-343-0358
www.bolloreinc.com

Bolloré

Rev. 8/1/2017

Bolphane® ShrinkFilm

Function	Grade & Thickness	Features
Standard Multi-purpose	BE 13-15-19-25	Strong shrink force center folded film with optimized perforation for controlled shrinkage, ideal for multipacking applications.
Standard High Speed	BX 50-60-75-100 gauge	High shrink force film with excellent stiffness and flatness, making it ideal for multipacking and high speed applications.
High Performance	BY 60-75-100 gauge	A 5-layer shrink film that seals and shrinks at lower temperatures with high free shrink for maximum retail presentation.
Ultra Thin	B30 30 gauge	High performance ultra thin shrink film, ultimate in source reduction and reduced carbon footprint.
Soft Shrink	BRX 45-60-75 gauge	Cross-linked shrink film that combines low force and high free shrink to wrap thin packages and irregularly shaped items.
Low Gauge	BLG 45 gauge	Cross-linked technology in a low gauge shrink film that combines material savings and abuse resistance
Superior Strength	BTTX110 40 gauge	Cross-linked shrink film with high seal strength
High Shrink	BTT+125 48 gauge	High shrink characteristics at low temperature
Antifog	BFF 45-60 gauge	Cross-linked shrink film with high performance antifog properties that deliver superior gloss and clarity.
Bio-based PE (produced from sugarcane ethanol)	B-NAT 60 gauge	The unique technical properties of B-Nat ensure excellent machine results, high seal strength and maximum retail presentation
High Performance Cross-linked	BCL 40-60-75-100 gauge	Cross-linked multi-purpose shrink film, with exceptional strength and puncture resistant. (125 & 150 gauge available with terms)