



Bolphane[®]
ShrinkFilm

PERFECT FIT



Bolloré, Inc.
60 Louisa Viens Dr
Dayville, CT 06241
Sales: 800-343-0358
www.bolloréinc.com

Rev. 6/01/2012

Bolloré

Bolphane® BTT+125

High Speed Polyolefin ShrinkFilm

- Enhanced stiffness for high speed machine compatibility
- Instant sealing
- High shrink characteristics at low temperature
- Hot slip properties
- Excellent optics & appearance



Bolphane® BTT+125 is ideally suited for application where high speed packaging equipment is running. Exceptional shrink characteristics on irregular shaped items.

Bolphane® BTT+125 can be successfully used in applications ranging from multimedia to publishing items as well as office supplies.

TECHNICAL FEATURES

Gauge	48	
Length of the roll (feet)	Singlewound	11,660
	Centerfolded	5,830
Gloss (20°)	114	
Haze (%)	3	
	LD*	TD**
Elongation at break (%)	100	110
Tensile strength (kg/cm ²)	1 150	1 100
Free Shrink(%)	at 200°F	30
	at 250°F	66

* LD: Longitudinal Direction – ** TD: Transverse Direction

» Please contact us for any specific request.

60, Louisa Viens Drive
P.O. Box 530 - Dayville, CT 06241-0530
Sales: 800-343-0358 • Tel: 860-774-7431
Fax: 860-774-8895 • www.bollforeinc.com



Bolloré